



colour laser printer

Office colour made easy



Phaser® 6180

Colour Laser Printer

Introducing fast colour performance to your office.

Leading the way among fast, affordable, easy-to-use colour laser printers, the Xerox Phaser 6180 delivers the speed and print quality today's small to medium-size businesses have been waiting for. High-performance features and unparalleled ease-of-use deliver spectacular results, page after page.

Step up the pace

The Phaser 6180 laser printer gets your jobs out quickly. Very quickly.

- A print speed of up to 20 ppm in full colour brings your work to colourful life without slowing you down.
- Print black and white – even complex or large jobs – at up to a speedy 25 ppm thanks to a powerful 400 MHz processor.
- A first-page-out time as quick as 10 seconds means your job's out faster than your walk to the printer.
- Flexible connectivity options, such as 10/100Base-TX Ethernet, USB, parallel and optional wireless adapter, give you the power to support the printing needs of your entire office.

Unleash your potential

With vibrant, true-to-life colours and crisp text and image definition, the Phaser 6180 prints like a pro.

- A print resolution of up to 600 x 600 x 4 dpi delivers sixteen shades of colour per pixel, producing exceptional photographic quality.
- Emulsion Aggregation (EA) High Gloss toner uses smaller, more uniform toner "particles" to bring more detail and clarity to every image.
- True Adobe® PostScript® 3™ print language ensures bright, vivid, accurate colours and graphics.
- Onboard colour capabilities, including PANTONE® Colour approved solid-colour simulations, Xerox colour correction technology and expert calibration tools, automatically give you the right colour or let you fine-tune colours for special applications.
- With the onboard duplexer (standard on DN configuration), the Phaser 6180 gives you fast, automatic two-sided printing.
- The 60,000-page-per-month duty cycle easily handles your demanding workload.



The user-friendly control panel features convenient onscreen status and toner-level indicators.





Designed to adapt to the dynamic needs of today's small to medium-size businesses.

- ① The 150-sheet Tray 1 (MPT) supports a wide range of custom media and sizes.
- ② A generous 250-sheet Tray 2 feeds up to 220 gsm media.
- ③ Add an optional 550-sheet feeder for a total input capacity of 950 sheets.
- ④ Fast, money-saving, two-sided printing is standard on the DN configuration.
- ⑤ Standard 128 MB memory is upgradable to 1,152 MB, allowing for seamless printing of even the most demanding, graphic-heavy print jobs.

Work hard, print easy

From installation to everyday operation, the Phaser 6180 laser printer provides a wealth of features to make office life easier.

- Included installation software is extremely fast and easy to use, getting you up and running in minutes with no IT required.
- Keep tabs on print jobs and get quick access to online support from the comfort of your chair with CentreWare® IS Embedded Web Server which works seamlessly with your browser.
- The front-panel toner gauge provides a quick, visual check of current toner levels, and user-friendly front access means no more moving the printer to replace supplies.
- Less consumables to change for greater ease-of-use.
- Built-in support for Apple Bonjour™ and included Mac drivers make the Phaser 6180 a true team player in PC/Mac environments.
- PrintingScout™ saves precious time by tracking print jobs and providing immediate print-issue alerts with correction suggestions.
- Super-quiet operation makes the Phaser 6180 laser printer office-friendly.





Call today. For more information, call **00-800-9000-9090** or visit us at **www.xerox.com/office**



CONFIGURATIONS		Phaser 6180N	Phaser 6180DN
Speed		Up to 20 ppm colour / 25 ppm black and white	
Duty Cycle		60,000 pages / month*	
Paper Handling			
Paper input	Standard	Tray 1 (MPT): 150 sheets; Custom sizes: 76.2 x 127 mm to 220 x 355.6 mm Tray 2: 250 sheets; Custom sizes: 148 x 210 mm to 220 x 355.6 mm	
	Optional	Tray 3: 550 sheets; Custom sizes: 148 x 210 mm to 220 x 355.6 mm	
Paper output		300 sheets	
Two-sided output		Optional	Standard
Print		As fast as 10 seconds colour	
First-page-out time			
Resolution (max)		600 x 600 x 4 dpi	
Processor		400 MHz	
Memory (std / max)		128 MB / 1152 MB	
Connectivity		10/100Base-TX Ethernet, USB 2.0, Parallel, Optional multi-protocol network card, Optional wireless network adapter	
Page Description Languages		Adobe® PostScript® 3™, PCL® 6 emulation	
Print features	Standard	Booklet printing, Covers, Separators, Transparency separators, N-up, Watermarks, Overlays, Poster printing, Banner sheets, Fit to page	
	Additional**	Secure Print, Proof Print, Ram collation	
Warranty		One-year on-site warranty	

* Print volume uniformly distributed over 30 days
 ** Requires minimum 256 MB RAM

Device Management

CentreWare® IS Embedded Web Server, CentreWare Web, PrintingScout™, MailInX email alerts

Print Drivers

Windows® 2000/XP/2003 Server, Vista, Mac OS®X version 10.2 or higher, Unix: Solaris™ 8/9/10, HP-UX® 11.0, AIX® 4.3.3, Linux: SUSE® 9.2/9.3, Turbo Linux™ 10, Red Hat® ES3/ES4, Fedora™ Core 1, Yellow Dog 3.X

Font Support

PostScript® fonts: 136; PCL® fonts: 81

Media Handling

Tray 1 (MPT), Tray 2, Tray 3 (optional): 65–220 gsm
 Two-sided output: 65–163 gsm
 Media types: Plain paper, glossy, envelopes, labels, transparencies, card stock, business card stock

Colour Standards

PANTONE® Colour approved solid-colour simulations, Colour correction tables

Operating Environment

Temperature: Storage: 0° to 35° C, operating: 10° to 32° C
 Humidity: 15% to 80%
 Sound pressure levels: Printing: 49.1 dB(A)
 Standby: 28.6 dB(A)
 Sound power levels: Printing: 6.62 B, Standby: 4 B
 Warm-up time (from sleep mode): 20 seconds

Electrical

Power: 110–127 VAC, 50/60 Hz or 220–240 VAC, 50/60 Hz
 Power consumption:
 110–127 VAC: Standby: 70 W
 Printing: 450 W
 Power save: 5.4 W
 220–240 VAC: Standby: 68.9 W
 Printing: 410 W
 Power save: 6.3 W
 ENERGY STAR® qualified

Physical Dimensions (WxDxH)

400 x 493 x 470 mm
 Weight: 27.2 kg, 6180DN: 28.3 kg
 Optional 550-sheet feeder:
 400 x 493 x 138 mm
 Weight: 7.7 kg

Certifications

FCC Part 15, Class B, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 73/23/EEC and 89/336/EEC, Section 508 ADA

Supplies

Standard-capacity print cartridge:

Black: 3,000 pages¹ 113R00722
 Cyan: 2,000 pages¹ 113R00719
 Magenta: 2,000 pages¹ 113R00720
 Yellow: 2,000 pages¹ 113R00721

High-capacity print cartridge:

Black: 8,000 pages¹ 113R00726
 Cyan: 6,000 pages¹ 113R00723
 Magenta: 6,000 pages¹ 113R00724
 Yellow: 6,000 pages¹ 113R00725

¹Average Continuous Composite CMY Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

Options

550-sheet feeder 097S03744
 256 MB Phaser memory 097S03743
 512 MB Phaser memory 097S03635
 Multi-protocol network card 097S03773
 Duplex unit 097S03746
 Wireless network adapter
 –European power converter 097S03741
 –UK power converter 097S03742

