

Detailed Specifications



*WorkCentre Pro 75
shown with optional 5,100-sheet High-Capacity Feeder
and Advanced Office Finisher.*



*WorkCentre Pro 90
shown with optional Professional Finisher.*

WorkCentre® Pro 75 Advanced Multifunction System

WorkCentre® Pro 90 Advanced Multifunction System

OUTPUT SPEED – printing and copying

75 images per minute (ipm) A4	90 images per minute (ipm) A4
37 ipm A3	45 ipm A3
37 ipm B4	45 ipm B4

FIRST-IMAGE-OUT TIME – A4, from platen to finisher top tray

6.8 seconds	6.0 seconds
-------------	-------------

WorkCentre® Pro 75/90

NETWORK PRINTING – SMart™ Network Controller

Processor	Intel® Celeron® 433 MHz
Memory	128 MB RAM (256 MB max)
System Disk	Minimum 9.1 GB
Printer Languages (auto sensing/ switching)	PostScript® 3 emulation TIFF PCL® 6 (PCL 5e) emulation PDF LCDS, SCS, XES and IPDS through third-party transforms

NETWORK PRINTING – resolution, printing via CentreWare® software

PostScript emulation: 600 x 600 dpi for 256 levels of grey: 1200 x 1200 dpi and 1800 x 1800 dpi for 256 levels of grey via patented emulation process.
PCL emulation: 600 x 600 dpi

WorkCentre® Pro 75/90 Advanced Multifunction Systems

NETWORK PRINTING – printing features*

Edge-to-edge printing
 Secure print
 Delay print (specific time)
 Sample set
 Booklet creation
 Cover selection
 Paper selection by attribute
 N-up
 Saddle-stitch booklet making (requires Professional Finisher)
 Folding (requires Professional Finisher)
 Watermark
 Fit to new paper size
 Transparency interleave
 Banner sheet enable/disable
 Output tray selection
 Image quality
 Store and recall driver settings

PRINT PROTOCOLS AND NETWORKS

Physical	Ethernet 100BaseT/10BaseT, 10Base2, 10Base5 via adapter IEEE 1284 parallel (compatibility mode) Wireless Ethernet (IEEE 802.11b) via third-party adapters USB printer port (optional)
Operating Systems	Microsoft Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®, Windows Server 2003 Novell® NetWare® 4.x, 5.x, 6 Mac OS® 8.x, 9.x, OS X Solaris® 2.5.1, 2.6 and higher HP-UX® 10.2, 11.x IBM AIX® 4.2 and higher Linux® Intel® – Red Hat® – Caldera® – Mandrake™ (LPRNG printing infrastructure) – Corel® (i386) – TurboLinux® (i386) – SuSE® (i386) Linux Power PC® – TurboLinux Server 6.0.2
Network Protocols	TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI

Continued

*Not all features are available in every driver.

WorkCentre® Pro 75/90 Advanced Multifunction Systems

PRINT PROTOCOLS AND NETWORKS *Continued*

Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet			
Fonts	PostScript 3: 136 PostScript standard fonts PCL: 80 scalable fonts, line printer and bitmap format line printer fonts Font Management Utility for downloading additional fonts			
Print Drivers	Environment	PCL5e	PCL 6	PostScript
	Windows 95/98/Me	Bidirectional enhanced*	Bidirectional enhanced*	Bidirectional enhanced*
	Windows 2000/XP/ Windows Server 2003 (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional enhanced	Bidirectional with user-selectable interface (standard** and enhanced)
	Macintosh® System 8.x, 9.x, OS X	N/A	N/A	Generic PPD
	Macintosh® System 9.x	N/A	N/A	Bidirectional via AppleTalk
Print Submission Tools	Environment	PCL		PostScript
	Solaris 2.5.1, 2.6 and higher; IBM AIX 4.2 and higher; LPRNG printing infrastructure; Linux Intel and Linux Power PC	Submission Tool only		Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 95/98/Me/NT 4.0/2000/XP	Submission Tool for any TIFF or PDF file		
CENTREWARE® INTERNET SERVICES – integrated device Web page				
Device Status	Web server embedded on SMart network controller – Tray status/contents – Consumables status			
Print Queue Viewing	Complete job printing queue management – hold, release, promote and delete			
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection			
Device Administration	Allows simple, remote installation setting of configuration options and management of the device			
Browsers	Windows XP/2000/NT 4.0/Me/98/95: Netscape Navigator® 6.x, Microsoft Internet Explorer 5.x/6.x Macintosh 9.x/OS X: Netscape Navigator 6.x Linux: Netscape® 6.x			

*Enhanced: Xerox custom graphical user interface.

**Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).

WorkCentre® Pro 75/90 Advanced Multifunction Systems

NETWORK SCANNING (optional)

Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan-to-network or fax jobs
Input Speed	65 ipm – (A4 long edge feed [LEF]) at all resolutions
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi 100 x 200 dpi
Maximum Scan Area	297 x 432 mm
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000) and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
Network Protocol	Novell (NCP via IPX/SPX) FTP via TCP/IP Microsoft SMB
File Formats	TIFF 6.0 with G3 MH and G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression
Document Management Fields	One to six user-programmable metadata fields per scan job Customised fields viewed on WorkCentre Pro user interface Variable data entered using virtual keyboard at WorkCentre Pro
Scan Destinations	Scan to network server Scan to remote e-mail destinations via direct SMTP addresses Scan to e-mail via optional CentreWare® Scanning Services using MAPI 32-bit compliant e-mail client Scan to application (workflow, Electronic Document Management System) Scan to Microsoft Exchange public folders Scan to PC Desktop™ (Standard and Deluxe editions) Scan to Windows XP client via Windows Image Acquisition (WIA)
Network Scanning With E-Mail Includes:	Scan to network directory Scan to e-mail distribution Scan to Xerox or third-party applications Scan to Windows XP client (requires WIA driver downloadable from xerox.com)
Scanning Software Options	Scan to PC Desktop Standard – includes everything in Network Scanning With E-mail, plus: – Xerox CentreWare Scanning Services – software tools that enhance the administration and use of template-based scanning – ScanSoft® PaperPort® SE 2.0 image viewing and file management software – ScanSoft OmniPage® SE 1.0 (for CW Distribution Server installation) and ScanSoft OmniPage SE 2.0 (for desktop/client installation) – OCR and file format conversion software Scan to PC Desktop Deluxe – everything in Network Scanning With E-mail, plus: – Xerox CentreWare Scanning Services – software tools that enhance the administration and use of template-based scanning – ScanSoft PaperPort Pro 9.0 Office – image viewing and file management/sharing software – ScanSoft OmniPage Pro 11.0 (for CW Distribution Server installation) and ScanSoft OmniPage Pro 12.0 Office (for desktop/client installation) – OCR and file format conversion software

WorkCentre® Pro 75/90 Advanced Multifunction Systems

E-MAIL (included with all network scanning options)

Capability	Direct document e-mail from the device Manual address entry or directory (Exchange/Notes™/LDAP) address searching
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi 100 x 200 dpi
Maximum Scan Area	297 x 432 mm
Network Protocol	SMTP, MIME encoded
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000) and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
Directory Access	Supports corporate address list via LDAPv3 (Exchange/Notes) Downloaded address list (comma-separated file format)
File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression

COPYING

Document Scanner	Duplex Automatic Document Feeder with 100-sheet capacity
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 dpi x 8 bit
Concurrency	Concurrent scanning and printing
Digital Imaging	AutoIQ automatic digital image quality control Auto rotation selection 90° or 270° when needed Image shift Edge erase Edge-to-edge copying Auto centering Original type selection (normal, text, halftone, photo) Lighter/darker Background suppression Contrast Sharpness Screening

Continued

WorkCentre® Pro 75/90 Advanced Multifunction Systems

COPYING *Continued*

Copy Pre-collation Memory	64 MB RAM standard Optional upgrade to 192 MB 9.1 GB disk storage (minimum)
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Annotation (user-editable comment, pagination, bates stamping and date stamp) Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up – up to six columns by six rows maximum for A4 Transparency dividers (blank or printed) Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, tabs, different paper sources and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher) Stapling (single/dual)
Foreign Device Interface/RS-232 Port (optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service PC interface for upload/download of internal auditron data
INTERNET FAX (optional)	
Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	297 x 432 mm/A3
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell Netware 4.x5.x6x Optional PIN-based guest login
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T.37 compliant

WorkCentre® Pro 75/90 Advanced Multifunction Systems

NETWORK FAX SERVER INTEGRATION (optional)

Provides walk-up faxing and hard-copy output of received faxes when integrated with third-party fax-server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.

<i>Fax Send Features</i>	One- or two-sided scanning (up to A3) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, halftone photo, photo, background suppression, seven levels of contrast, seven levels of sharpness)
<i>Fax Print Features</i>	One- or two-sided printing (up to A3) Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
<i>Authentication</i>	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell® NetWare 4.x/5.x/6.x Optional PIN-based guest login
<i>Supported Network Fax Vendors</i>	Multiple vendors, certified by the Xerox Alliance Partners Programme. For details, visit www.xerox.com .

DEVICE MANAGEMENT

<i>Management Support</i>	SNMP Version 1 and SNMP Version 2c trap MIB access (IETF-MIB II RFC 1213), host resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
<i>CentreWare Network Services</i>	Device Discovery wizard (available at www.xerox.com) Device Administration wizard (available at www.xerox.com) Font management utility
<i>Xerox CentreWare Web</i>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) and Internet Explorer 5.01 or higher.
<i>Novell NDPS/NEPS (gateway for WorkCentre Pro)</i>	Server gateway application: centralised management tool provides streamlined installations via printer agents, automated printer driver installation and downloads, printer and job configuration, configurable event notification.

Continued

WorkCentre® Pro 75/90 Advanced Multifunction Systems

DEVICE MANAGEMENT *Continued*

Xerox CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View. Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk.
Xerox CentreWare® for Tivoli® NetView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by Tivoli NetView. Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet. Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC).
Xerox CentreWare® MC for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server in NT and Windows 2000 environments. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by HP OpenView. Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons. Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView.
Xerox Plug and Print 2000	Plug and Print 2000 (PnP2000) is an administrative service programme that simplifies enterprise-wide printer installs and relocations for Windows 2000 environments. The product discovers devices, automatically installs devices, enables sharing printers to users and provides install reports – all through a user-friendly interface.
Xerox Barcode Pro PS (Optional)	Enables intelligent PostScript barcode printing on Xerox multifunction systems by storing Xerox software as well as the barcode fonts on the printer hard disk. This solution enables the printing of barcodes from any application (client or mainframe) that supports PostScript® printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL): – Simplex or duplex printing – Finishing – single or dual stapling – Tray pull location from six different trays – Print security via PIN ID capability at the WorkCentre Pro
Xerox SAP R/3 PostScript Intelligent Barcode Utility (optional) Purchase via www.font.net	Provides built-in process intelligence that allows the automated printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox PostScript Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.

PAPER HANDLING—Duplex Automatic Document Feeder (DADF)

Capacity*	100 sheets
Document Feeder Scan Speed	65 images per minute – A4 long edge feed (LEF)
Paper Sizes Sensed	A5 LEF or short edge feed (SEF) A4 LEF or SEF B4 SEF A3 SEF
Weights	60 to 120 gsm

*Paper capacities are based on 75 gsm stock: capacities will vary with different weight stocks.

WorkCentre® Pro 75/90 Advanced Multifunction Systems

PAPER HANDLING – Front-Loading Paper Trays

Number	Four
Capacity*	500 sheets each
Sizes	User adjustable from A5 to A3 Service adjustable for 305 x 457 mm
Weights	60 to 200 gsm
Types	Letterhead Preprinted forms Labels Transparencies Hole-punched Recycled paper Bond Index Cover Tab stock Card stock

PAPER HANDLING – Bypass Tray

Capacity*	50 sheets
Sizes	A6 to 305 x 457 mm
Weights	60 to 200 gsm

PAPER HANDLING – 3,100-sheet High-Capacity Feeder (HCF) (75 standard)

Capacity*	3,100 sheets
Paper Size	A4 LEF
Weights	60 to 120 gsm
Total Capacity*	5,150 sheets (with Bypass Tray, Four Trays and High-Capacity Feeder)

PAPER HANDLING – 5,100-sheet High-Capacity Feeder (HCF) (WCP 75 optional, 90 standard)

Capacity*	5,100 sheets
Paper Size	A4 LEF
Weights	60 to 120 gsm
Total Capacity*	7,150 sheets (with Bypass Tray, Four Trays and High-Capacity Feeder)

PAPER HANDLING – A3 Large Capacity Kit (optional with 5,100-sheet HCF)

Capacity* and paper sizes	5,100 sheets A4 LEF 2,500 sheets A3 SEF
Weights	60 to 120 gsm

PAPER HANDLING – Convenience Stapler and Work Surface (optional)

Capacity*	Up to 50 sheets 5,000 staples per cartridge
------------------	--

*Paper capacities are based on 75 gsm stock: capacities will vary with different weight stocks.

WorkCentre® Pro 75/90 Advanced Multifunction Systems

OUTPUT OPTIONS

**Office Finisher
(50-sheet stapling)**
Top Tray

Capacity:* 250 sheets
Paper Sizes: A6 to 305 x 457 mm

Main Tray

Capacity:* 2,000 sheets
Paper Sizes: 182 x 257 mm to 305 x 457 mm
Weights: 60 to 200 gsm
Stapling Positions: Single and dual, portrait and landscape orientations
Maximum Stapler Capacity:* 50 sheets

**Advanced Office Finisher
(100-sheet stapling)**
Top Tray

Capacity:* 250 sheets
Paper Sizes: A6 to 305 x 457 mm

Main Tray

Capacity:* 2,000 sheets
Paper Sizes: 182 x 257 mm to 305 x 457 mm
Weights: 60 to 200 gsm
Stapling Positions: Single and dual, portrait and landscape orientations
Maximum Stapler Capacity:* 100 sheets for A4 and below; 50 sheets for larger sizes

Professional Finisher
Top Tray

Capacity:* 250 sheets
Paper Sizes: A6 to 305 x 457 mm

Main Tray

Capacity:* 2,000 sheets
Paper Sizes: 182 x 257 mm to 305 x 457 mm
Weights: 60 to 200 gsm
Stapling Positions: Single and dual, portrait and landscape orientations
Maximum Stapler Capacity:* 100 sheets for A4 and below; 50 sheets for larger sizes

Booklet Maker

Capacity:* Tray stop up, 30 booklets (one to five sheets per booklet); tray stop down, unlimited
Paper Sizes: A4, B4, A3
Weights: 60 to 200 gsm
Saddle-Stitch Capacity:* 2 to 15 sheets (8 to 60 page booklet)
V-Fold Capacity:* One to five sheets (unstapled)

Tri-Folder

Capacity:* Tray stop up, 55 sheets; tray stop down, unlimited
Paper Sizes: A4
Weights: 60 to 90 gsm
Folding: Single-sheet folds (single-sided and double-sided), C and Z shapes

*Paper capacities are based on 75 gsm stock: capacities will vary with different weight stocks.

WorkCentre® Pro 75/90 Advanced Multifunction Systems

ACCOUNTING

Accounting With Third-Party Server Applications (optional) Up-to-the-minute data on how the WorkCentre Pro system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax. Multiple accounting vendors, certified by the Xerox Alliance Partners Programme. For details, visit www.xerox.com.

Internal Auditor Tracks copy use only; supports up to 2,500 user accounts (1 to 12 digits) or 11,000 general accounts (5 digits) Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software.

WorkCentre® Pro 75
Advanced Multifunction System

WorkCentre® Pro 90
Advanced Multifunction System

BASIC CONFIGURATIONS*

3,100-sheet High-Capacity Feeder
Office Finisher
Network Controller

5,100-sheet High-Capacity Feeder
Office Finisher
Network Controller

WorkCentre® Pro 75/90

ACCESSORIES

Office Finisher (50-sheet stapling)
Advanced Office Finisher (100-sheet stapling)
Professional Finisher (100-sheet stapling, saddle-stitch booklet making, tri-folding)
Convenience Stapler
3,100-sheet High-Capacity Feeder (WCP 75 standard)
5,100-sheet High-Capacity Feeder (WCP 75 optional, WCP 90 standard)
A3 Large Capacity Kit (optional with 5,100 sheet HCF)
Image Overwrite Security
Foreign Device Interface/RS-232 port
Copy Pre-collation 128 MB RAM Upgrade
Network Scanning With E-Mail
Scan to PC Desktop Client Software
Network Fax Server Integration
Network Accounting Enablement
Network Controller RAM Upgrade 128 MB (to 256 MB maximum)
USB Printing Port
Internet Fax
SAP R/3 PostScript Intelligent Barcode Utility

*Features, configurations and options may vary by location.

WorkCentre® Pro 75
Advanced Multifunction System
WorkCentre® Pro 90
Advanced Multifunction System
ELECTRICAL REQUIREMENTS

Sole use of 220 - 240 volt, 10 ampere, 50 Hz circuit;
 Advanced Office and Professional Finisher requires a
 separate 220 - 240 volt, 10 ampere, 50 Hz circuit

Sole use of 120/240 volts (or) 208Y/120-127 volts, 3 wire
 + PE (Protective Earth), 16 ampere, 60Hz, NEMA 14-20R
 receptacle.

POWER CONSUMPTION

Running	1,440 watts with 50-sheet Stapling Finisher	1,870 watts with 50-sheet Stapling Finisher
	1,880 watts with 100-sheet Stapling Finisher	2,310 watts with 100-sheet Stapling Finisher or Professional Finisher
Standby	360 watts	341 watts
Low-Power Mode	339 watts	280 watts
Sleep Mode	65 watts	59 watts
Warm-up	Four minutes	Three minutes
Low-Power Recovery	30 seconds (maximum)	30 seconds (maximum)

ENVIRONMENTAL CONSIDERATIONS

Required Temperature Range	10° to 35° C	10° to 35° C
Required Relative Humidity	10% to 90%	10% to 90%
Noise Emission	39.4 dBA standby; 62.9 dBA operating; 69.0 dBA impulse	38.5 dBA standby; 64.2 dBA operating; 70.0 dBA impulse
Heat Emission	1,230 BTU/hr standby; 4,915 BTU/hr operating	1,165 BTU/hr standby; 6,356 BTU/hr operating
Ozone Emission	< 0.01 parts per million	< 0.01 parts per million

WorkCentre® Pro 75/90

DIMENSIONS AND WEIGHT

	<i>Width</i>	<i>Depth</i>	<i>Height</i>	<i>Weight</i>
<i>Fully Configured With 50-Sheet Stapling Office Finisher</i>	1,753 mm	930 mm	1,359 mm	245 kg
<i>Fully Configured With 100-Sheet Stapling Advanced Office Finisher</i>	2,032 mm	930 mm	1,359 mm	278 kg
<i>Fully Configured With Professional Finisher</i>	2,235 mm	930 mm	1,359 mm	312 kg

SPACE REQUIREMENTS*

	<i>Width</i>	<i>Depth</i>	<i>Height</i>
<i>Fully Configured With 50-Sheet Stapling Office Finisher</i>	2,591 mm	1,974 mm	1,981 mm
<i>Fully Configured With 100-Sheet Stapling Advanced Office Finisher</i>	2,718 mm	1,974 mm	1,981 mm
<i>Fully Configured With Professional Finisher</i>	2,769 mm	1,974 mm	1,981 mm

*No additional space required for A3 Large Capacity Kit or Convenience Stapler.

CERTIFICATIONS

FCC Class B Compliant (U.S.), DOC Class B Compliant (Canada)
 89/336/EEC (Europe)
 UL Listed (UL 1950, Third Edition)
 CB Certified (IEC 60950/EN 60950)
 73/23/EEC (Europe)
 95/5/EEC (Europe)
 WHQL, Novell NetWare

WorkCentre® Pro 75/90				
SUPPLIES				
Description	Order Number	No. per Box	Expected Yield	
Dry Ink Cartridge	6R90321	6	23,500 (65); 24,500 (75); 28,000 (90); per cartridge at 6% area coverage	
Convenience Stapler Staple Cartridge	108R53	3	5,000 staples per cartridge	
Staple Cartridge (for Office [50-sheet stapling] Finisher)	108R53	3	5,000 staples per cartridge	
Staple Housing Cartridge (for Advanced Office [100-sheet stapling] Finisher and Professional Finisher)	8R12912	1	N/A	
Staples for Staple Housing Cartridge (for Advanced Office [100-sheet stapling] Finisher and Professional Finisher)	8R12898	3	5,000 staples per cartridge	
Professional Finisher Booklet Maker Staples	8R12897	8	2,000 staples per cartridge	
Note: Staple Housing Cartridge comes filled with 5,000 staples.				

